



# LexEVS 5.x Analytical Grid Service API

[LexEVS 5.x Query Service Extension](#) > [LexEVS 5.x Value Domain Service](#) > [LexEVS 5.x Pick List Service](#) > [LexEVS 5.x caCORE Data Service API](#) > [LexEVS 5.x Analytical Grid Service API](#)

## Contents [hide]

- 1 Introduction
- 2 Using the API
- 3 Method Descriptions
  - 3.1 getCodingSchemeConcepts
  - 3.2 getFilter
  - 3.3 getSortAlgorithm
  - 3.4 getFilterExtensions
  - 3.5 getServiceMetadata
  - 3.6 getSupportedCodingSchemes
  - 3.7 getLastUpdateTime
  - 3.8 resolveCodingScheme
  - 3.9 getNodeGraph
  - 3.10 getMatchAlgorithms
  - 3.11 getGenericExtensions
  - 3.12 getGenericExtension
  - 3.13 getHistoryService
  - 3.14 getSortAlgorithms
  - 3.15 resolveCodingSchemeCopyright
  - 3.16 setSecurityToken
- 4 Usage Instructions
  - 4.1 Service URL
  - 4.2 Required Libraries
  - 4.3 Downloads
- 5 Code Examples
  - 5.1 Example client and service calls, and SOAP messages
  - 5.2 Example API usage
- 6 Error Handling
  - 6.1 Error Connecting to LexEVS Grid Service
  - 6.2 LexEVS Errors
  - 6.3 Invalid Service Context Access
- 7 Security Issues

## Introduction

This document is a section of the [Programmer's Guide](#).

The following table summarizes the operations available through the LexEVS Analytical Grid Service. Each of the operations is also defined in detail below. The grid analytical service and related operations are viewable via the caGrid Portal (<http://cagrid-portal.nci.nih.gov> ).

## Using the API

There are two (2) different interfaces for accessing the LexEVS Grid Services:

1. org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter, or
2. org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter

Option 1, org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter provides an interface for interacting with the LexEVS Grid Services. This Interface is intended to mirror the existing LexEVS API as much as possible. There is no object wrapping for semantic purposes on this interface. This allows existing applications of the LexEVS API to use Grid Services without code changes.

### vocabkc contents

- [Main Page](#)
- [What's New](#)
- [Forums](#)
- [Bugzilla](#)
- [Code Repository](#)
- [Feedback](#)
- [Contact Us](#)

### tools

- [LexBIG/LexEVS](#)
- [LexWiki](#)
- [NCI Protégé](#)
- [Related Tools and Models](#)

### projects

- [LexAjax](#)
- [LexGrid](#)
- [Cancer Data Standards Repository \(caDSR\)](#)
- [Common Terminology Criteria for Adverse Events \(CTCAE\)](#)
- [Open Health Natural Language Processing \(OHNLP\) Consortium](#)
- [Ontology Development and Information Extraction \(ODIE\)](#)

### semantic infrastructure

- [SI Main Page](#)
- [Initiatives](#)
- [Requirements](#)

### other resources

- [Library of Documents](#)
- [Documentation and Training for Tools](#)
- [Index of Terminologies](#)
- [Standards and Standards Influencing Organizations](#)
- [Outreach](#)

### external links

- [VCDE Workspace](#)
- [caBIG@ Community Website](#)
- [caBIG@ Support Service Providers](#)

### help

- [Editing Wiki Pages](#)

- [Editing Forum Posts](#)
- [Contact Us](#)

search

toolbox

- [What links here](#)
- [Related changes](#)
- [Upload file](#)
- [Special pages](#)
- [Printable version](#)
- [Permanent link](#)
- [Print as PDF](#)

This Interface may be acquired by instantiating LexBIGServiceAdapter with the Grid Service URL as a parameter.

```
LexBIGService lbs = new LexBIGServiceAdapter
("http://lexevsapi-analytical50.nci.nih.gov/wsrp/services/cagrid/LexEVSGridService");
```

Option 2, org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter also provides an interface for interacting with the LexEVS Grid Services. However, this Interfaces is the semantically defined interface. All method parameters and return values are defined and annotated as CDEs to be loaded into caDSR. This Interface is intended to be caGrid Silver Level Compliant.

This Interface may be acquired by instantiating LexBIGServiceGridAdapter with the Grid Service URL as a parameter.

```
LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter
("http://lexevsapi-analytical50.nci.nih.gov/wsrp/services/cagrid/LexEVSGridService");
```

## Method Descriptions

### getCodingSchemeConcepts

getCodingSchemeConcepts(CodingSchemeIdentification, CodingSchemeVersionOrTag)	
Description:	Returns the set of all (or all active) concepts in the specified coding scheme.
Input:	org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification, org.LexGrid.LexBIG.DataModel.Core.CodingSchemeVersionOrTag
Output:	org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.CodedNodeSet.stubs.types.CodedNodeSetReference
Exception:	RemoteException
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Create a Resource on the server and populate it with the requested org.LexGrid.LexBIG.LexBIGService.CodedNodeSet.</p> <p><i>Step 2:</i> Return the Client Reference to the user. This Reference has the above org.LexGrid.LexBIG.LexBIGService.CodedNodeSet as a Resource. An org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.CodedNodeSetClient object is built from the above Reference.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Build a org.LexGrid.LexBIG.DataModel.Core.CodingSchemeVersionOrTag containing the Version information for the desired Coding Scheme <pre>CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion("testVersion");</pre> <p><i>Step 3:</i> Build an org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification to hold the Coding Scheme name. <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> <p><i>Step 4:</i> Invoke the LexBIG caGrid service as follows: CodedNodeSetGrid cns = lbs.getCodingSchemeConcepts(codingScheme, csvt); </p></p></p>

### getFilter

getFilter(ExtensionIdentification)	
Description:	Returns an instance of the filter extension registered with the given name.
Input:	org.LexGrid.LexBIG.DataModel.cagrid.ExtensionIdentification
Output:	org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Filter.stubs.types.FilterReference
Exception:	RemoteException
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Create a Resource on the server and populate it with the requested org.LexGrid.LexBIG.Extensions.Query.Filter</p>

*Step 2:* Return the Client Reference to the user. This Reference has the above `org.LexGrid.LexBIG.Extensions.Query.Filter` as a Resource. This client is a Service Context that allows the user to call regular `org.LexGrid.LexBIG.Extensions.Query.Filter` API calls through the grid service. An `org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Filter.client.FilterClient` object is built from the above Reference. This `FilterClient` implements the Interface `org.LexGrid.LexBIG.Extensions.Query.Filter`. This makes calling Grid Service Calls through `org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Filter.client.FilterClient` transparent to the end user.

**Sample Call:**

*Step 1:* Connect to the LexEVS caGrid Service using the `org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter` or `org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter`

```
LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);
```

*Step 2:* Build an `org.LexGrid.LexBIG.DataModel.cagrid.ExtensionIdentification` to hold the Extension name.

```
ExtensionIdentification extension = new ExtensionIdentification();
extension.setLexBIGExtensionName(name);
```

*Step 3:* Invoke the LexEVS caGrid service as follows:

```
Filter filter = lbs.getFilter(extension);
```

## getSortAlgorithm

getSortAlgorithm(ExtensionIdentification)	
Description:	Returns an instance of the sort extension registered with the given name.
Input:	<code>org.LexGrid.LexBIG.DataModel.cagrid.ExtensionIdentification</code>
Output:	<code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort</code> stubs.types.SortReference
Exception:	<code>RemoteException</code>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Create a Resource on the server and populate it with the requested <code>org.LexGrid.LexBIG.Extensions.Query.Sort</code></p> <p><i>Step 2:</i> Return the Client Reference to the user. This Reference has the above <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort.client.SortClient</code> as a Resource. This client is a Service Context that allows the user to call regular <code>org.LexGrid.LexBIG.Extensions.Query.Sort</code> API calls through the grid service. An <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort.client.SortClient</code> object is built from the above Reference. This <code>SortClient</code> implements the Interface <code>org.LexGrid.LexBIG.Extensions.Query.Sort</code>. This makes calling Grid Service Calls through <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort.client.SortClient</code> transparent to the end user.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code></p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Build an <code>org.LexGrid.LexBIG.DataModel.cagrid.ExtensionIdentification</code> to hold the Extension name.</p> <pre>ExtensionIdentification extension = new ExtensionIdentification(); extension.setLexBIGExtensionName(name);</pre> <p><i>Step 3:</i> Invoke the LexEVS caGrid service as follows:</p> <pre>Filter filter = lbs.getSortAlgorithm(extension);</pre>

## getFilterExtensions

getFilterExtensions()
-----------------------

Description:	Returns a description of all registered extensions used to provide additional filtering of query results.
Input:	<i>none</i>
Output	<i>org.LexGrid.LexBIG.DataModel.Collections.ExtensionDescriptionList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the <i>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</i> or <i>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</i></p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Invoke the LexEVS caGrid service as follows:</p> <pre>ExtensionDescriptionList extDescList = lbs.getFilterExtensions();</pre>

## getServiceMetadata

<b>getServiceMetadata()</b>	
Description:	Return an interface to perform system-wide query over metadata for loaded code systems and providers.
Input:	<i>none</i>
Output:	<i>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.LexBIGServiceMetadata.stubs.types.LexBIGServiceMetadataReference</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Create a Resource on the server and populate it with the requested <i>org.LexGrid.LexBIG.LexBIGService.LexBIGServiceMetadata</i></p> <p><i>Step 2:</i> Return the <i>LexBIGServiceMetadataClient</i> to the user. This <i>LexBIGServiceMetadataClient</i> has the above <i>org.LexGrid.LexBIG.LexBIGService.LexBIGServiceMetadata</i> as a Resource. An <i>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.LexBIGServiceMetadataClient</i> object is built from the above Reference.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the <i>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</i> or <i>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</i></p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Invoke the LexEVS caGrid service as follows:</p> <pre>LexBIGServiceMetadataGrid metadata = lbs.getServiceMetadata();</pre>

## getSupportedCodingSchemes

<b>getSupportedCodingSchemes()</b>	
Description:	Return a list of coding schemes and versions that are supported by this service, along with their status.
Input:	<i>none</i>
Output:	<i>org.LexGrid.LexBIG.DataModel.Collections.CodingSchemeRenderingList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p>

**Sample Call:**

```

Step 1: Connect to the LexEVS caGrid Service using the
org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or
org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter
LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);
Step 2: Invoke the LexEVS caGrid service as follows:
CodingSchemeRenderingList csrl = lbs.getSupportedCodingSchemes();

```

## getLastUpdateTime

getLastUpdateTime()	
Description:	Return the last time that the content of this service was changed; null if no changes have occurred. Tag assignments do not count as service changes for this purpose.
Input:	none
Output:	java.util.Date
Exception:	RemoteException
Implementation Details:	<p><b>Implementation:</b></p> <p>Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <pre> Step 1: Connect to the LexEVS caGrid Service using the org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url); Step 2: Invoke the LexEVS caGrid service as follows: Date date = lbs.getLastUpdateTime(); </pre>

## resolveCodingScheme

resolveCodingScheme(CodingSchemeIdentification, CodingSchemeVersionOrTag)	
Description:	Return detailed coding scheme information given a specific tag or version identifier.
Input:	org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification, org.LexGrid.LexBIG.DataModel.Core.CodingSchemeVersionOrTag
Output:	org.LexGrid.codingSchemes.CodingScheme
Exception:	RemoteException
Implementation Details:	<p><b>Implementation:</b></p> <p>Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <pre> Step 1: Connect to the LexEVS caGrid Service using the org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url); Step 2: Build an org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification to hold the Coding Scheme name. CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code); Step 3: Build a org.LexGrid.LexBIG.DataModel.Core.CodingSchemeVersionOrTag containing the Version information for the desired Coding Scheme CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion("testVersion"); </pre>

*Step 4:* Invoke the LexEVS caGrid service as follows: CodedNodeSetGrid cns = lbs.resolveCodingScheme(codingScheme, csvt);

## getNodeGraph

getNodeGraph(CodingSchemeIdentification, CodingSchemeVersionOrTag, RelationContainerIdentification)	
Description:	Returns the node graph as represented in the particular relationship set in the coding scheme.
Input:	<i>org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification, org.LexGrid.LexBIG.DataModel.Core.CodingSchemeVersionOrTag, org.LexGrid.LexBIG.DataModel.cagrid.RelationContainerIdentification</i>
Output:	<i>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.CodedNodeGraph.stubs.types.CodedNodeGraphReference</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Create a Resource on the server and populate it with the requested <i>org.LexGrid.LexBIG.LexBIGService.CodedNodeGraph</i>.</p> <p><i>Step 2:</i> Return the Client Reference to the user. This Reference has the above <i>org.LexGrid.LexBIG.LexBIGService.CodedNodeGraph</i> as a Resource. An <i>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.CodedNodeGraphClient</i> object is built from the above Reference.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexBIG caGrid Service using the <i>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</i> or <i>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</i></p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Build an <i>org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification</i> to hold the Coding Scheme name.</p> <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> <p><i>Step 3:</i> Build an <i>org.LexGrid.LexBIG.DataModel.Core.CodingSchemeVersionOrTag</i> containing the Version information for the desired Coding Scheme</p> <pre>CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion("testVersion");</pre> <p><i>Step 4:</i> Build an <i>org.LexGrid.LexBIG.DataModel.cagrid.RelationContainerIdentification</i> containing the Relation Container information.</p> <pre>RelationContainerIdentification container = new RelationContainerIdentification(); container.setDc(name);</pre> <p><i>Step 5:</i> Invoke the LexEVS caGrid service as follows, providing String parameters for the desired Coding Scheme and Relationship Name: CodedNodeGraphGrid cng = client.getNodeGraph(codingScheme, csvt, container);</p>

## getMatchAlgorithms

getMatchAlgorithms()	
Description:	Returns the node graph as represented in the particular relationship set in the coding scheme.
Input:	<i>none</i>
Output:	<i>org.LexGrid.LexBIG.DataModel.Collections.ModuleDescriptionList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p>

```

Step 1: Connect to the LexEVS caGrid Service using the
org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or
org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter

LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);

Step 2: Invoke the LexEVS caGrid service as follows: ModuleDescriptionList mdl =
lbs.getMatchAlgorithms();

```

## getGenericExtensions

getGenericExtensions()	
Description:	Returns a description of all registered extensions used to implement application-specific behavior that is centrally accessible from a LexBIGService. Note that only generic extensions (base class GenericExtension) will be listed here. All other classes are retrievable at the appropriate interface point (filter, sort, etc).
Input:	<i>none</i>
Output:	<i>org.LexGrid.LexBIG.DataModel.Collections.ExtensionDescriptionList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p>Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <p>Step 1: Connect to the LexEVS caGrid Service using the org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</p> <p>Step 2: Invoke the LexEVS caGrid service as follows: ExtensionDescriptionList edl = lbs.getGenericExtensions();</p>

## getGenericExtension

getGenericExtensions(ExtensionIdentification)	
Description:	Returns an instance of the application-specific extension registered with the given name.
Input:	<i>org.LexGrid.LexBIG.DataModel.cagrid.ExtensionIdentification</i>
Output:	<i>org.LexGrid.LexBIG.DataModel.Collections.SortDescriptionList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p>Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <p>Step 1: Connect to the LexEVS caGrid Service using the org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</p> <p>NOTE: Currently this method will return a LexBIGServiceConvenienceMethods instance.</p> <p>Step 2: Build an org.LexGrid.LexBIG.DataModel.cagrid.ExtensionIdentification to hold the Extension name. ExtensionIdentification <code>extension = new ExtensionIdentification();</code> <code>extension.setLexBIGExtensionName("LexBIGServiceConvenienceMethods");</code></p> <p>Step 3: Invoke the LexEVS caGrid service as follows: LexBIGServiceConvenienceMethodsGrid lbscm = lbs.getGenericExtensions(extension);</p> <p>Step 4: Return the LexBIGServiceConvenienceMethodsClient to the user. This LexBIGServiceConvenienceMethodsClient has the above</p>



org.LexGrid.LexBIG.Extensions.Generic.LexBIGServiceConvenienceMethods as a Resource. An org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.CodedNodeGraphClient object is built from the above Reference.

## getHistoryService

getHistoryService(CodingSchemeIdentification)	
Description:	Resolve a reference to the history api servicing the given coding scheme.
Input:	org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification
Output:	org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices. HistoryService.stubs.types.HistoryServiceReference
Exception:	RemoteException
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><i>Step 2:</i> Return the HistoryServiceClient to the user. This HistoryServiceClient has the above org.LexGrid.LexBIG.History.HistoryService as a Resource. This Client is a Service Context that allows the user to call regular org.LexGrid.LexBIG.History.HistoryService API calls through the grid service. HistoryServiceClient implements the Interface org.LexGrid.LexBIG.History.HistoryService. This makes calling Grid Service Calls through org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.HistoryService.client.HistoryServiceClient transparent to the end user.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Build an org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification to hold the Coding Scheme name.</p> <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> <p><i>Step 3:</i> Invoke the LexEVS caGrid service as follows: HistoryServiceGrid history = lbs.getHistoryService(codingScheme);</p>

## getSortAlgorithms

getSortAlgorithms(SortContext)	
Description:	Returns a description of all registered extensions used to provide additional filtering of query results.
Input:	org.LexGrid.LexBIG.DataModel.InterfaceElements.types.SortContext
Output:	org.LexGrid.LexBIG.DataModel.Collections.SortDescriptionList
Exception:	RemoteException
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter or org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Invoke the LexEVS caGrid service as follows: SortDescriptionList sortDesclList = lbs.getSortAlgorithms(sortContext);</p>



## resolveCodingSchemeCopyright

resolveCodingSchemeCopyright(CodingSchemeIdentification)	
Description:	Return coding scheme copyright given a specific tag or version identifier.
Input:	<i>org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification</i>
Output:	<i>org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeCopyRight</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code></p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Build an <code>org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name.</p> <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification();</pre> <pre>codingScheme.setCode(code);</pre> <p><i>Step 3:</i> Build an <code>org.LexGrid.LexBIG.DataModel.Core.CodingSchemeVersionOrTag</code> containing the Version information for the desired Coding Scheme</p> <pre>CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion("testVersion");</pre> <p><i>Step 4:</i> Invoke the LexEVS caGrid service as follows: <code>CodingSchemeCopyRight copyright = lbs.resolveCodingSchemeCopyright(codingScheme, csvt);</code></p>

## setSecurityToken

setSecurityToken(CodingSchemeIdentification, SecurityToken)	
Description:	Sets the Security Token for the given Coding Scheme.
Input:	<i>org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification, gov.nih.nci.evs.security.SecurityToken</i>
Output:	<i>org.LexGrid.LexBIG.cagrid.LexEVSGridService.stubs.types.LexEVSGridServiceReference.LexEVSGridServiceReference</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p><b>Implementation:</b></p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p><b>Sample Call:</b></p> <p><i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code></p> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <p><i>Step 2:</i> Build an <code>org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name.</p> <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setName("codingScheme");</pre> <p><i>Step 3:</i> Build an <code>gov.nih.nci.evs.security.SecurityToken</code> containing the security information for the desired Coding Scheme.</p> <pre>SecurityToken metaToken = new SecurityToken(); metaToken.setAccessToken("token");</pre> <p><i>Step 4:</i> Invoke the LexEVS caGrid service as follows: This will return a reference to a new "LexBIGServiceGrid"</p>

instance that is associated with the security properties that were passed in.

```
LexBIGServiceGrid lbsg = lbs.setSecurityToken(codingScheme, metaToken);
```

## Usage Instructions

### Service URL

The LexEVS Grid Service 4.2 URL is: <http://lexevsapi.nci.nih.gov/wsrf/services/cagrid/LexEVSGridService>.

The service is also accessible via the [caGRID Portal](#).

### Required Libraries

The libraries required for programmatic access to the LexEVS Grid Service are listed in the tables below. The 3rd Party Software Libraries required for use of the LexEVS API Grid Service are listed in Table 4.1 and the NCICB software captured under the caBIG® umbrella are listed in Table 4.2.

Table 4.1 3rd Party Libraries

Product	Jars	License	Home Page
Apache WS-Addressing	addressing-1.0.jar	<a href="#">addressing 1.0.LICENSE</a>	From Globus 4.0.2 Java Web Services Core lib directory: <a href="http://www.globus.org/toolkit/downloads/4.0.2">http://www.globus.org/toolkit/downloads/4.0.2</a> Source available at <a href="http://ws.apache.org/addressing">http://ws.apache.org/addressing</a>
Apache Axis	axis-ant.jar axis.jar commons-pool-1.3.jar commons-logging-1.1.jar commons-lang-2.2.jar commons-collections-3.2.jar commons-codec-1.3.jar log4j-1.2.8.jar jaxrpc.jar saaj.jar wsdl4j.jar	<a href="#">axis-jars.LICENSE</a>	<a href="http://ws.apache.org/axis">http://ws.apache.org/axis</a>
Apache Xerces	xercesImpl.jar	<a href="#">xerces.LICENSE</a>	<a href="http://xerces.apache.org/xerces-j">http://xerces.apache.org/xerces-j</a>
Apache Lucene	lucene-core-2.3.2.jar lucene-regex-2.3.2.jar lucene-snowball-2.3.2.jar	<a href="#">Lucene LICENSE</a>	<a href="http://lucene.apache.org/">http://lucene.apache.org/</a>
ASM - all purpose Java bytecode manipulation and analysis framework	asm.jar	<a href="http://asm.objectweb.org/license.html">http://asm.objectweb.org/license.html</a>	<a href="http://asm.objectweb.org/">http://asm.objectweb.org/</a>

Castor	castor-1.2.jar	<a href="http://www.castor.org/license.html">http://www.castor.org/license.html</a>	<a href="http://www.castor.org/index.html">http://www.castor.org/index.html</a>
Globus Toolkit	cog-axis.jar cog-jglobus.jar	<a href="http://www.globus.org/toolkit/legal/4.0/">http://www.globus.org/toolkit/legal/4.0/</a>	
Bouncy Castle Crypto APIs	jce-jdk13-125.jar	<a href="http://www.bouncycastle.org/licence.html">http://www.bouncycastle.org/licence.html</a>	<a href="http://www.bouncycastle.org/">http://www.bouncycastle.org/</a>
Open Permis	wsrf_core.jar wsrf_core_stubs.jar	<a href="http://www.openpermis.org/BSDlicenceKent.txt">http://www.openpermis.org/BSDlicenceKent.txt</a>	<a href="http://www.openpermis.org/">http://www.openpermis.org/</a>
Apache WSS4J	wss4j.jar	<a href="http://ws.apache.org/wss4j/license.html">http://ws.apache.org/wss4j/license.html</a>	<a href="http://ws.apache.org/wss4j/">http://ws.apache.org/wss4j/</a>
Spring	spring.jar	<a href="#">Spring LICENSE</a>	<a href="http://www.springframework.org">http://www.springframework.org</a>

Table 4.2 NCICB/caBIG Libraries

Library	Associated JARs
caGrid Software Libraries	caGrid-ServiceSecurityProvider-client-1.2.jar
	caGrid-ServiceSecurityProvider-common-1.2.jar
	caGrid-ServiceSecurityProvider-stubs-1.2.jar
	caGrid-core-1.2.jar
	caGrid-metadata-common-1.2.jar
	caGrid-metadata-data-1.2.jar
	caGrid-metadata-security-1.2.jar
	caGrid-metadatautils-1.2.jar
EVS API Libraries	evsapi42-beans.jar
	evsapi42-framework.jar
LexEVS Grid Service Client Library	LexEVSGridService-client.jar
LexEVS Grid Service Stubs	LexEVSGridService-stubs.jar
LexEVS Grid Service Common	LexEVSGridService-common.jar
LexEVS Grid Service Service	LexEVSGridService-service.jar
LexEVS Grid Service Tests	LexEVSGridService-tests.jar
caCORE SDK Library	sdk-client-framework.jar
LexEVS API	lexbig.jar
Custom Castor Serializer	castor-bean-serializer.jar

## Downloads

For your convenience, the required libraries are available for download here:

<https://gforge.nci.nih.gov/docman/view.php/491/14401/lexevs42-gridsvc-jars.jar>

In order to programmatically access the LexEVS API Grid Service, these libraries need to be added to your local classpath.

## Code Examples

Example client and service calls, and SOAP messages

See <http://gforge.nci.nih.gov/docman/view.php/491/14252/TestClient.zip>

Example API usage

Example 1: Searching for concepts in NCI Thesaurus containing the string "Gene"

```
//Create a Connection to the Grid Service
LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(gridServiceURL);

//Set up the CodingSchemeIdentification object to define the Coding Scheme</font>
CodingSchemeIdentification csid = new CodingSchemeIdentification();
```

```

csid.setName("NCI Thesaurus");

//Get the CodedNodeSet for that CodingScheme (This returns a CodedNodeSet Service Context)
CodedNodeSetGrid cmsg = lbs.getCodingSchemeConcepts(csid, null);
//getCodingSchemeConcepts is a Grid Service Call

//Set the text to match
MatchCriteria matchText = new MatchCriteria();
matchText.setText("Gene");
//Define a SearchDesignationOption, if any
SearchDesignationOption searchOption = new SearchDesignationOption();

//Choose an algorithm to do the matching
ExtensionIdentification matchAlgorithm = new ExtensionIdentification();
matchAlgorithm.setLexBIGExtensionName("contains");

//Chose a language
LanguageIdentification language = new LanguageIdentification();
language.setIdentifier("en");

//Restrict the CodedNodeSet
cmsg.restrictToMatchingDesignations(matchText, searchOption, matchAlgorithm, language);
//restrictToMatchingDesignations is a Grid Service Call

//Create a SetResolutionPolicy to handle the details of Resolving the CodedNodeSet
//Here, we will set the Maximum number of Concepts returned to 10.
SetResolutionPolicy resolvePolicy = new SetResolutionPolicy();
resolvePolicy.setMaximumToReturn(10);

//Do the resolve
ResolvedConceptReferenceList rcrlist = cmsg.resolveToList(resolvePolicy);
//resolveToList is a Grid Service Call

//Use the returned ResolvedConceptReferenceList to print some details about the concepts found
ResolvedConceptReference[] rcref = rcrlist.getResolvedConceptReference();
for (int i = 0; i < rcref.length; i++) {
    System.out.println(rcref[i].getConceptCode());
    System.out.println(rcref[i].getReferencedEntry().
        getPresentation()[0].getText().getContent());
}

```

## Error Handling

### Error Connecting to LexEVS Grid Service

When connecting through the Java Client, `java.net.ConnectException` and `org.apache.axis.types.URI.MalformedURIException` may be thrown upon an unsuccessful attempt to connect.

A `MalformedURIException` is thrown in the case if a poorly-formed URL string. In this case, the exception is thrown before an attempt to connect is even made.

If the URL is well-formed, proper connection is tested. If the connection attempt fails, a `ConnectException` is thrown containing the reason for the failure.

```

try{
    LexBIGServiceGridAdapter lbsg = new LexBIGServiceGridAdapter
        ("http://localhost:8080/wsrf/services/cagrid/LexEVSGridService");
} catch (java.net.ConnectException e){
    //Error Connecting
    e.printStackTrace();
} catch (org.apache.axis.types.URI.MalformedURIException e){
    //URL Syntax Error
    e.printStackTrace();
}

```

This example shows a typical connection to the LexEVS Grid Service, with the two potential Exceptions being caught and handled as necessary.

### LexEVS Errors

LexEVS errors will be forwarded through the Distributed LexEVS layer and then on to the Grid layer. Input parameters, along with any other LexEVS (or Distributed LexEVS) errors will be detected on the server, not the client, and forwarded. All Generic LexEVS (or Distributed LexEVS) errors will be forwarded via a `RemoteException`, with the cause of the error and underlying LexEVS error message included.

### Invalid Service Context Access

Service Context Services are not meant to be called directly. If the client attempts to do so, an `org.LexGrid.LexBIG.cagrid.LexEVSGridService.CodedNodeSet.stubs.types.InvalidServiceContextAccess` Exception will be thrown. This indicates a call was made to a Service Context without obtaining a Service Context Reference via the Main Service (see the above section Service Contexts and State for more information).

### Security Issues

## LexEVS Grid Service Security

Certain vocabulary content accessible through the LexEVS Grid Service may require extra authorization to access. Each client is required to supply its own access credentials via Security Tokens. These Security Tokens are implemented by a SecurityToken object:

**Name:** SecurityToken **Namespace:** gme://caCORE.caCORE/3.2/gov.nih.nci.evs.security **Package:** gov.nih.nci.evs.security

### Accessing Secure Content

A client establishes access to a secured vocabulary via the following Grid Service Calls:

*Step 1:* Connect to the LexEVS caGrid Service `LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);`

*Step 2:* Build an `org.LexGrid.LexBIG.DataModel.cagrid.CodingSchemeIdentification` to hold the Coding Scheme name.

`CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setName("codingScheme");`

*Step 3:* Build an `gov.nih.nci.evs.security.SecurityToken` containing the security information for the desired Coding Scheme.

`SecurityToken token = new SecurityToken (); token.setAccessToken("securityToken");`

*Step 4:* Invoke the LexEVS caGrid service as follows: This will return a reference to a new "LexBIGServiceGrid" instance that is associated with the security properties that were passed in.

`LexBIGServiceGrid lbsg = lbs.setSecurityToken(codingScheme, token);`

It is important to note that the Grid Service "setSecurityToken" returns an `org.LexGrid.LexBIG.cagrid.LexEVSGridService.stubs.types.LexEVSGridServiceReference.LexEVSGridServiceReference` object. This reference must be used to access the secured vocabularies.

### Implementation

Each call to "setSecurityToken" sets up a secured connection to Distributed LexEVS with the access privileges included in the SecurityToken parameter. The LexEVSGridServiceReference that is returned to the client contains a unique key identifier to the secure connection that has been created on the server. All subsequent calls the client makes through this LexEVSGridServiceReference will be made securely. If additional SecurityTokens are passed in through the "setSecurityToken" Grid Service, the additional security will be added and maintained.

The "setSecurityToken" Grid Service is a stateful service. This means that after the client sets a SecurityToken, any subsequent call will be applied to that SecurityToken.

Secure connections are not maintained on the server indefinitely, but are based on load conditions. The server will allow 30 unique secure connections to be set up for clients without any time limitations. As additional requests for secure connections are received by the server, connections will be released by the server on an 'oldest first' basis. No connection, however, may be released prior to 5 minutes after its creation.

If no SecurityTokens are passed in by the client, a non-secure Distributed LexEVS connection will be used. The server maintains one (and only one) un-secured Distributed LexEVS connection that is shared by any client not requesting security.

### NOTE:

All non-secured information accessed by the LexEVS Grid Service is publicly available from NCICB and users are expected to follow the licensing requirements currently in place for accessing and using NCI EVS information.

[Categories: VKC Contents](#) | [Documentation](#) | [LexEVS Code](#) | [LexEVS](#)



This page was last modified on 20 January 2010, at 15:26.

This page has been accessed 132 times.

[CONTACT US](#) | [PRIVACY NOTICE](#) | [DISCLAIMER](#) | [ACCESSIBILITY](#) | [APPLICATION SUPPORT](#)

