

LexEVS 6.0 Design Document - Detailed Design - Single DB

Document Information

Author: Craig Stancl
Email: Stancl.craig@mayo.edu
Team: LexEVS
Contract: CBITT BOA Subcontract# 29XS223
Client: NCI CBIIT
National Institutes of Health
US Department of Health and Human Services

Revision History

Version	Date	Description of Changes	Author
1.0	5/14/10	Initial Version Approved via Design Review	Team

This document describes use of a Single Database Table versus Multiple Database Tables.

LexEVS 6.0 will include an option to load CodingSchemes into a single, common set of tables, or individual sets of tables for each CodingSchemes. Some considerations for each option:

- Single Table Advantages:
 - Limits Table proliferation in the database.
 - All Coding Schemes centralized into one table.
- Single Table Disadvantages:
 - Possible performance penalty. A query will be executed against the common table, which will be many times larger than the ontology loaded as an individual table.

To the underlying API, the actual table that data is stored in will be abstracted. All queries will except a Prefix -- whether that prefix is from the common table, or from an individual table, the query remains the same.

The prefix will be stored in the *registry* table of the database. The prefixed is then obtained given a CodingScheme URI and Version. Every CodingScheme will be loaded in the Registry, and the prefix will be retrievable given its URI and Version.

registry
«column»
*PK registryGuid: VARCHAR2(36)
resourceURI: VARCHAR2(250)
resourceVersion: VARCHAR2(50)
resourceType: VARCHAR2(50)
dbURI: VARCHAR2(250)
dbName: VARCHAR2(50)
prefix: VARCHAR2(20)
status: VARCHAR2(50)
tag: VARCHAR2(50)
lastUpdateDate: TIMESTAMP
activationDate: TIMESTAMP
deactivationDate: TIMESTAMP
baseRevision: VARCHAR2(50)
fixedAtRevision: VARCHAR2(50)
isLocked: CHAR(1)
dbSchemaVersion: VARCHAR2(50)
dbSchemaDescription: VARCHAR2(255)
«PK»
+ PK_registry(VARCHAR2)
«unique»
+ UQ_registry(VARCHAR2, VARCHAR2, VARCHAR2)

registryMetaData
«column»
lastUpdateTime: TIMESTAMP
lastUsedDBIdentifier: VARCHAR2(50)
lastUsedHistoryIdentifier: VARCHAR2(50)

resourceType:

1. CodingScheme
2. ValueDomain
3. PickList
4. NCIHistory

Prefixes are automatically injected into SQL statements to direct the SQL to the appropriate table. For instance:

```
SELECT FROM $prefix$entity WHERE ...
```

Prior to the execution of the SQL statement, the '\$prefix\$' placeholder will be replaced with the actual prefix retrieved from the Registry.