

Installing OWL2 Vocabularies in LexEVS 6.1

Contents of this Page

- [LexEVS 6.1 OWL2 Loader Script](#)

LexEVS Administration Links

- [Admin Guide Main Page](#)
 - [Admin with LexEVS GUI](#)
 - [Admin with Command Line](#)
 - [Management and Admin API](#)
 - [Advanced Vocab Admin](#)
- [LexEVS 6.0 Main Page](#)
- [LexEVS Current Release](#)

LexEVS 6.1 has all the administrative capabilities of LexEVS 6.0 as well as the following loader functions:

LexEVS 6.1 OWL2 Loader Script

Shell Script	Use and Function
LoadOWL2	<p>Loads an OWL file. You can provide a manifest file to configure coding scheme# meta data.</p> <p>Options:</p> <ul style="list-style-type: none">• <code>-in,--input <uri></code> URI or path specifying location of the source file• <code>-mf,--manifest <uri></code> URI or path specifying location of the manifest file• <code>-lp,--loaderPrefs<uri></code> URI or path specifying location of the loader preference file• <code>-v, --validate <int></code> Perform validation of the candidate resource without loading data. If specified, the '-a' and '-t' options are ignored. Supported levels of validation include:<ul style="list-style-type: none">• 0 = Verify document is well-formed• 1 = Verify document is valid• <code>-a, --activate</code> ActivateScheme on successful load; if unspecified the vocabulary is loaded but not activated.• <code>-t, --tag <id></code> An optional tag ID (e.g. 'PRODUCTION' or 'TEST') to assign. <p>Load Example:</p> <pre>LoadOWL2 -in "file:///path/to/somefile.owl" -a</pre> <pre>LoadOWL2 -in "file:///path/to/somefile.owl" -v 0</pre>

: