caNanoLab 2.3 Installation Guide

Welcome to the caNanoLab 2.3 Installation Guide.



Topics in this document include:

- Introduction to caNanoLab
- Open Source Technologies
- Obtaining the caNanoLab Source Code
- Ant Build Properties
 Setting Data
 - Setting Properties
 Installation and Deployment
- Verification

Introduction to caNanoLab

For more information about the 2.3 updates, refer to the caNanoLab 2.3 Release Notes.

Return to top

Open Source Technologies

Download each of the following tools and follow the installation instructions provided with each respective product for your environment. Assistance from a MySQL database administrator is expected to properly configure the MySQL database. For MySQL database configuration and maintenance, it is also helpful to download the MySQL workbench (suite of GUI tools) at http://www.mysql.com/downloads/workbench/

Product	Link
Java Software Development Kit (JDK) version 8.0 and set JAVA_HOME	http://www.oracle.com/technetwork/java/javase/downloads/jdk8-downloads-2133151.html
Wildfly version 8.2.0.Final	http://wildfly.org/downloads/ 🗗
Jakarta Ant version 1.9.x and set ANT_HOME environment variable	http://archive.apache.org/dist/ant/binaries/
MySQL version 5.1.x	http://dev.mysql.com/downloads/mysql/5.1.html
Apache Maven 3.3.x or higher	https://archive.apache.org/dist/maven/maven-3

Return to top

Obtaining the caNanoLab Source Code

Downloads for caNanoLab are available at caNanoLab GitHub Repository.

The caNanoLab Software License applies.

Return to top

Ant Build Properties

Setting Properties

Follow these steps to set the build and deploy properties required for building and deploying caNanoLab.

Step 1. Extract caNanoLab

Extract the GitHub location to a location on your local system, for example, C:\caNanoLab_2.3. and navigate into the "software" directory to reach the source. (This location is referred as <CANANOLAB_SOURCE> throughout the document). Verify that the following five folders exist in the directory <CANANOLAB_SOURCE>:

- build
- cananolab-db
- cananolab-grid
- cananolab-webapp
- common

Return to top

Step 2. Edit Ant Properties

Edit the Ant properties file, build.properties, at <CANANOLAB_SOURCE>/build by specifying values for the following properties.

Property	Description
file. repository.dir	A directory on the system that hosts the Wildfly application server for storing uploaded files, for example, C:/apps/caNanoLab.
	Writable Directory Create this directory prior to starting the application, and ensure that the user who starts the Wildfly server has Write
	access. If working on Windows platform, use either double back slashes \\ or a single forward slash / as the file separator.
admin.email	The email address that receives requests for new user accounts, for example, the NCI CBIIT application support email for the NCI CBIIT installation, for example, nciclit@mail.nih.gov .
ldap. authenticatio n.enabled	A Boolean flag to indicate whether or not to use LDAP for user authentication. caNanoLab 2.1.1 and beyond does not support LDAP authentication. Set this to false.
database. server	The name of the server hosting the database, for example, localhost.
database.port	The database port number, for example, 3306.
database. user	The database user name used in the caNanoLab application, for example, cananolab_app.
database. password	The password for the database that the user specified above, for example, go!234.
database. system.user	The system database user name with privileges to create a database, create tables, and grant user accesses to a database, for example, root.
database. system. password	The password for the system database that the user specified above, for example, rootpass.
jboss.server.	The Wildfly server directory, for example:
	C:/apps/wildfly-8.2.0.Final/standalone

Return to top

Installation and Deployment

Step 1. DB changes to be deployed to migrate to caNanoLab 2.3 from caNanoLab 2.1

a Execute the following scripts in the order specified below:

• https://github.com/CBIIT/cananolab/blob/cananolab-2.3-it-11/software/cananolab-webapp/db-scripts/2.3/caNanoLab22.sql

Return to top

Step 2. caNanoLab installation instructions to upgrade to 2.3

a Follow these steps to deploy the caNanoLab application.

Action

1	Set up an environment variable JBOSS_HOME to point to the Wildfly installation directory.
	(i) Windows Platform
	If working on the Windows platform, use either double back slashes // or a single forward slash / as the file separator, for example, J BOSS_HOME=C:/wildfly-8.2.0.Final (C:\wildfly-8.2.0.Final would fail).
2	Execute the Ant build script build.xml located at <cananolab_source>/software/cananolab-webapp/build.xml with the target dist.</cananolab_source>
	Example: Issue the following commands to execute the Ant script:
	C:\>cd C:\caNanoLab_2.3\software\cananolab-webapp C:\caNanoLab_2.3\software\cananolab-webapp>ant dist
	Successful execution of the Ant script generates the following artifacts that include two deployable web archive war files, configuration files and libraries for running the web application in the Wildfly environment, and also places these artifacts in the appropriate directories under <jboss_home>. Artifacts generated are also available in the following folder under <cananolab_source>:</cananolab_source></jboss_home>
	target/dist/cananolab-webapp/caNanoLab.war
	target/dist/common/mysgl-connector-java-5.1.26.jar
	<pre>target/dist/common/properties-service.xml</pre>
	target/dist/common/bcprov-jdk15on-1.47.jar
	target/dist/common/caNanoLab_modules.cli
	target/dist/common/caNanoLab_setup.cli
	target/dist/common/wikihelp.properties
3	We recommend increasing the JBoss JVM heap size to 2G bytes and permanent generation (permgen) memory space to 256M bytes by updating the file <jboss_home>/bin/standalone.conf with the following JAVA_OPTS:</jboss_home>
	JAVA OPTS="-Xms512m -Xmx2048m -XX:PermSize=128m
	-XX:MaxPermSize=256m -Dsun.rmi.dgc.client.gcInterval=3600000
	-Dsun.rmi.dgc.server.gcInterval=3600000"
	This configuration file is read when Wildfly server starts.
	For a standalone server, pass in the JVM settings either as command line arguments when executing the \$JBOSS_HOME/bin/standalone.sh
	script, or by declaring them in \$JBOSS_HOME/bin/standalone.conf.
	(For Windows users, the script to execute is %JBOSS_HOME%/bin/standalone.bat while the JVM settings can be declared in %JBOSS_HOME%/bin/standalone.conf.bat.)
4	Create a new directory structure C:/local/content/caNanoLab/artifacts and move the following artifacts.
	• caNanoLab.war
	• bcprov-jdk15on-1.47.jar
	• mysql-connector-java-5.1.26.jar
	caNanoLab_modules.cli
	• caNanoLab_setup.cli
	Create a new directory structure C:/local/content/caNanoLab/config and move the following artifacts.
	• ApplicationSecurityConfig.xml
	• wikihelp.properties



Return to top

b Migrate access control data from CSM 5.2 to Spring Security.

The migration of access control data has been implemented as a series of ReST services. These services must be invoked in the following order for all access data to be migrated from CSM to Spring Security.

#	Action
1	Migrates all user accounts and grants them all the default Public role and Curator role to curators in CSM.
	http://localhost:8080/caNanoLab/rest/datamigration/migrateuseraccounts
2	Migrates all access for samples - RWD access for owner and curator, R access for researcher, RWD and R access for specific users.
	http://localhost:8080/caNanoLab/rest/datamigration/migratesampleaccess
3	Migrates all access for protocols - RWD access for owner and curator, R access for researcher, RWD and R access for specific users.
	http://localhost:8080/caNanoLab/rest/datamigration/migrateprotocolaccess
4	Migrates all access for publications - RWD access for owner and curator, R access for researcher, RWD and R access for specific users.
	http://localhost:8080/caNanoLab/rest/datamigration/migratepublicationaccess
5	Adds all charaterizations to the ACL tables and sets them up with the corresponding sample as parent objects. This sets up the characterizations to inherit the access of their sample.
	http://localhost:8080/caNanoLab/rest/datamigration/migratecharaccess
6	Migrates all organizations to ACL tables and grant public access. Also, sets up inheritance of access for POCs of organizations.
	http://localhost:8080/caNanoLab/rest/datamigration/migratesamplesourceaccess

Return to top

c Restart the application server after the above step to migrate data is completed.

Verification

Once the deployment artifacts are deployed and the Wildfly application server is correctly configured, shutdown and restart the Wildfly application server, which in turn starts the caNanoLab application.

Open the URL, http://<APP_SERVER_URL>/caNanoLab/, for example, http://localhost:8080/caNanoLab . The Welcome/Login page appears.

Return to top