

3 - LexEVS 6.x Analytical Grid Service API (Deprecated -- Removed in 6.3)

Contents of this Page

- [Introduction](#)
- [ISO 21090 Model](#)
- [Using the API](#)
- [Method Descriptions](#)
 - [getCodingSchemeConcepts](#)
 - [getFilter](#)
 - [getSortAlgorithm](#)
 - [getFilterExtensions](#)
 - [getServiceMetadata](#)
 - [getSupportedCodingSchemes](#)
 - [getLastUpdateTime](#)
 - [resolveCodingScheme](#)
 - [getNodeGraph](#)
 - [getMatchAlgorithms](#)
 - [getGenericExtensions](#)
 - [getGenericExtension](#)
 - [getHistoryService](#)
 - [getSortAlgorithms](#)
 - [resolveCodingSchemeCopyright](#)
 - [setSecurityToken](#)
- [Usage Instructions](#)
 - [Service URL](#)
 - [Required Libraries](#)
 - [Downloads](#)
- [Code Examples](#)
 - [Example Client and Service Calls, and SOAP Messages](#)
 - [Example API Usage](#)
- [Error Handling](#)
 - [Error Connecting to LexEVS Grid Service](#)
 - [LexEVS Errors](#)
 - [Invalid Service Context Access](#)
- [Security Issues](#)
 - [LexEVS Grid Service Security](#)
 - [Accessing Secure Content](#)
 - [Implementation](#)

LexEVS 6.x Programmers Links

- [Programmer's Guide Main Page](#)
 - [LexEVS API](#)
 - [LexEVS 6.0 CTS2 API](#)
 - [LexEVS 6.x CTS2 API Quick Start](#)
- [Value Set and Pick List Guide](#)
- [LexEVS 6.0 Main Page](#)
- [LexEVS Current Release](#)

Introduction

The Analytical Grid Service is an API used by programmers to pull data from the system (a target instance of LexEVS on the grid) using a set of method calls and appropriate parameters. The results differ from method to method but are all objects in the LexEVS model.

The following table summarizes the operations available through the LexEVS Analytical Grid Service. Each of the operations is also defined in detail below. The grid analytical service and related operations are viewable via the [caGrid Portal](#).

Grid services are no longer supported

As of LexEVS 6.2 Grid services are no longer supported

ISO 21090 Model

The LexEVS 6.0 Analytical Grid Services use a version of the LexGRID/LexBIG model, extended to support ISO 21090 Datatypes.

Click the [adapted model link](#).

Using the API

There are two (2) different interfaces for accessing the LexEVS Grid Services:

- 1. `org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter`, or
- 2. `org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter`

- **Option 1, `org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter`** provides an interface for interacting with the LexEVS Grid Services. This Interface is intended to mirror the existing LexEVS API as much as possible. There is no object wrapping for semantic purposes on this interface. This allows existing applications of the LexEVS API to use Grid Services without code changes. This Interface may be acquired by instantiating `LexBIGServiceAdapter` with the Grid Service URL as a parameter.

```
LexBIGService lbs = new LexBIGServiceAdapter
("http://lexevsapi-analytical60.nci.nih.gov/wsrf/services/cagrid/LexEVSGridService");
```

- **Option 2, `org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter`** also provides an interface for interacting with the LexEVS Grid Services. However, this Interfaces is the semantically defined interface. All method parameters and return values are defined and annotated as CDEs to be loaded into caDSR. This Interface is intended to be caGrid Silver Level Compliant. This Interface may be acquired by instantiating `LexBIGServiceGridAdapter` with the Grid Service URL as a parameter.

```
LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter
("http://lexevsapi-analytical60.nci.nih.gov/wsrf/services/cagrid/LexEVSGridService");
```

Method Descriptions

getCodingSchemeConcepts

`getCodingSchemeConcepts(CodingSchemeIdentification, CodingSchemeVersionOrTag)`

Description:	Returns the set of all (or all active) concepts in the specified coding scheme.
Input:	<i>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification, org.LexGrid.LexBIG.iso21090.DataModel.Core.CodingSchemeVersionOrTag</i>
Output:	<i>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.CodedNodeSet.stubs.types.CodedNodeSetReference</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p>Implementation :</p> <ul style="list-style-type: none">• <i>Step 1:</i> Create a Resource on the server and populate it with the requested <code>org.LexGrid.LexBIG.LexBIGService.CodedNodeSet</code>.• <i>Step 2:</i> Return the Client Reference to the user. This Reference has the above <code>org.LexGrid.LexBIG.LexBIGService.CodedNodeSet</code> as a Resource. An <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.CodedNodeSetClient</code> object is built from the above Reference.

Sample Call	<p>Sample Call :</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <div data-bbox="376 254 1484 325"> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> </div> Step 2: Build a <code>org.LexGrid.LexBIG.iso21090.DataModel.Core.CodingSchemeVersionOrTag</code> containing the Version information for the desired Coding Scheme. <div data-bbox="376 413 1484 510"> <pre>CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion("testVersion");</pre> </div> Step 3: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name. <div data-bbox="376 598 1484 695"> <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> </div> Step 4: Invoke the LexBIG caGrid service as follows: <div data-bbox="376 762 1484 833"> <pre>CodedNodeSetGrid cns = lbs.getCodingSchemeConcepts(codingScheme, csvt);</pre> </div>
--------------------	--

getFilter

`getFilter(ExtensionIdentification)`

Description:	Returns an instance of the filter extension registered with the given name.
Input:	<code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.ExtensionIdentification</code>
Output:	<code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Filter.stubs.types.FilterReference</code>
Exception:	<code>RemoteException</code>
Implementation Details:	<p>Implementation :</p> <ul style="list-style-type: none"> Step 1: Create a Resource on the server and populate it with the requested <code>org.LexGrid.LexBIG.Extensions.Query.Filter</code>. Step 2: Return the Client Reference to the user. This Reference has the above <code>org.LexGrid.LexBIG.Extensions.Query.Filter</code> as a Resource. This client is a Service Context that allows the user to call regular <code>org.LexGrid.LexBIG.Extensions.Query.Filter</code> API calls through the grid service. An <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Filter.client.FilterClient</code> object is built from the above Reference. This <code>FilterClient</code> implements the Interface <code>org.LexGrid.LexBIG.Extensions.Query.Filter</code>. This makes calling Grid Service Calls through <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Filter.client.FilterClient</code> transparent to the end user.

Sample Call	<p>Sample Call :</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> Step 2: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.ExtensionIdentification</code> to hold the Extension name. <pre>ExtensionIdentification extension = new ExtensionIdentification(); extension.setLexBIGExtensionName(name);</pre> <ul style="list-style-type: none"> Step 3: Invoke the LexEVS caGrid service as follows: <pre>Filter filter = lbs.getFilter(extension);</pre>
--------------------	---

getSortAlgorithm

`getSortAlgorithm(ExtensionIdentification)`

Description:	Returns an instance of the sort extension registered with the given name.
Input:	<code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.ExtensionIdentification</code>
Output:	<code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort.stubs.types.SortReference</code>
Exception:	<code>RemoteException</code>
Implementation Details:	<p>Implementation :</p> <ul style="list-style-type: none"> Step 1: Create a Resource on the server and populate it with the requested <code>org.LexGrid.LexBIG.Extensions.Query.Sort</code> Step 2: Return the Client Reference to the user. This Reference has the above <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort.client.SortClient</code> as a Resource. This client is a Service Context that allows the user to call regular <code>org.LexGrid.LexBIG.Extensions.Query.Sort</code> API calls through the grid service. An <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort.client.SortClient</code> object is built from the above Reference. This <code>SortClient</code> implements the Interface <code>org.LexGrid.LexBIG.Extensions.Query.Sort</code>. This makes calling Grid Service Calls through <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.Sort.client.SortClient</code> transparent to the end user.
Sample Call	<p>Sample Call :</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> Step 2: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.ExtensionIdentification</code> to hold the Extension name. <pre>ExtensionIdentification extension = new ExtensionIdentification(); extension.setLexBIGExtensionName(name);</pre> <ul style="list-style-type: none"> Step 3: Invoke the LexEVS caGrid service as follows: <pre>Filter filter = lbs.getSortAlgorithm(extension);</pre>

getFilterExtensions

`getFilterExtensions()`

Description:	Returns a description of all registered extensions used to provide additional filtering of query results.
Input:	<i>none</i>
Output	<i>org.LexGrid.LexBIG.iso21090.DataModel.Collections.ExtensionDescriptionList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p>Implementation: <i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call:</p> <ul style="list-style-type: none"> <i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> <i>Step 2:</i> Invoke the LexEVS caGrid service as follows: <pre>ExtensionDescriptionList extDescList = lbs.getFilterExtensions();</pre>

getServiceMetadata

getServiceMetadata()

Description:	Return an interface to perform system-wide query over metadata for loaded code systems and providers.
Input:	<i>none</i>
Output:	<i>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.LexBIGServiceMetadata.stubs.types.LexBIGServiceMetadataReference</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p>Implementation:</p> <ul style="list-style-type: none"> <i>Step 1:</i> Create a Resource on the server and populate it with the requested <code>org.LexGrid.LexBIG.LexBIGService.LexBIGServiceMetadata</code>. <i>Step 2:</i> Return the <code>LexBIGServiceMetadataClient</code> to the user. This <code>LexBIGServiceMetadataClient</code> has the above <code>org.LexGrid.LexBIG.LexBIGService.LexBIGServiceMetadata</code> as a Resource. An <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.LexBIGServiceMetadataClient</code> object is built from the above Reference.
Sample Call	<p>Sample Call:</p> <ul style="list-style-type: none"> <i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> <i>Step 2:</i> Invoke the LexEVS caGrid service as follows: <pre>LexBIGServiceMetadataGrid metadata = lbs.getServiceMetadata();</pre>

getSupportedCodingSchemes

getSupportedCodingSchemes()

Description:	Return a list of coding schemes and versions that are supported by this service, along with their status.
Input:	<i>none</i>

Output:	<i>org.LexGrid.LexBIG.iso21090.DataModel.Collections.CodingSchemeRenderingList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p>Implementation: Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call:</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> Step 2: Invoke the LexEVS caGrid service as follows: <pre>CodingSchemeRenderingList csrl = lbs.getSupportedCodingSchemes();</pre>

getLastUpdateTime

`getLastUpdateTime()`

Description:	Return the last time that the content of this service was changed; null if no changes have occurred. Tag assignments do not count as service changes for this purpose.
Input:	<i>none</i>
Output:	<i>java.util.Date</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p>Implementation: Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call:</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> Step 2: Invoke the LexEVS caGrid service as follows: <pre>Date date = lbs.getLastUpdateTime();</pre>

resolveCodingScheme

`resolveCodingScheme(CodingSchemeIdentification, CodingSchemeVersionOrTag)`

Description:	Return detailed coding scheme information given a specific tag or version identifier.
Input:	<i>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification, org.LexGrid.LexBIG.iso21090.DataModel.Core.CodingSchemeVersionOrTag</i>
Output:	<i>org.LexGrid.codingSchemes.CodingScheme</i>
Exception:	<i>RemoteException</i>

Implementation Details:	<p>Implementation : Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call :</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> Step 2: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name. <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> <ul style="list-style-type: none"> Step 3: Build a <code>org.LexGrid.LexBIG.iso21090.DataModel.Core.CodingSchemeVersionOrTag</code> containing the Version information for the desired Coding Scheme. <pre>CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion("testVersion");</pre> <ul style="list-style-type: none"> Step 4: Invoke the LexEVS caGrid service as follows: <pre>CodedNodeSetGrid cns = lbs.resolveCodingScheme(codingScheme, csvt);</pre>
--------------------------------	--

getNodeGraph

`getNodeGraph(CodingSchemeIdentification, CodingSchemeVersionOrTag, RelationContainerIdentification)`

Description:	Returns the node graph as represented in the particular relationship set in the coding scheme.
Input:	<code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code> , <code>org.LexGrid.LexBIG.iso21090.DataModel.Core.CodingSchemeVersionOrTag</code> , <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.RelationContainerIdentification</code>
Output:	<code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.CodedNodeGraph.stubs.types.CodedNodeGraphReference</code>
Exception:	<code>RemoteException</code>
Implementation Details:	<p>Implementation :</p> <ul style="list-style-type: none"> Step 1: Create a Resource on the server and populate it with the requested <code>org.LexGrid.LexBIG.LexBIGService.CodedNodeGraph</code>. Step 2: Return the Client Reference to the user. This Reference has the above <code>org.LexGrid.LexBIG.LexBIGService.CodedNodeGraph</code> as a Resource. An <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.CodedNodeGraphClient</code> object is built from the above Reference.

Sample Call	<p>Sample Call :</p> <ul style="list-style-type: none"> Step 1: Connect to the LexBIG caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <div data-bbox="376 254 1484 325"> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> </div> Step 2: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name. <div data-bbox="376 415 1484 510"> <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> </div> Step 3: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.Core.CodingSchemeVersionOrTag</code> containing the Version information for the desired Coding Scheme. <div data-bbox="376 600 1484 695"> <pre>CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion("testVersion");</pre> </div> Step 4: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.RelationContainerIdentification</code> containing the Relation Container information. <div data-bbox="376 785 1484 879"> <pre>RelationContainerIdentification container = new RelationContainerIdentification(); container.setDc(name);</pre> </div> Step 5: Invoke the LexEVS caGrid service as follows, providing String parameters for the desired Coding Scheme and Relationship Name: <div data-bbox="376 970 1484 1041"> <pre>CodedNodeGraphGrid cng = client.getNodeGraph(codingScheme, csvt, container);</pre> </div>
--------------------	---


getMatchAlgorithms

getMatchAlgorithms()

Description:	Returns the node graph as represented in the particular relationship set in the coding scheme.
Input:	<i>none</i>
Output:	<i>org.LexGrid.LexBIG.iso21090.DataModel.Collections.ModuleDescriptionList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p>Implementation: Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p>Sample Call:</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <div data-bbox="376 1614 1484 1686"> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> </div> Step 2: Invoke the LexEVS caGrid service as follows: <div data-bbox="376 1755 1484 1827"> <pre>ModuleDescriptionList mdl = lbs.getMatchAlgorithms();</pre> </div>

getGenericExtensions


getGenericExtensions()

Description:	<p>Returns a description of all registered extensions used to implement application-specific behavior that is centrally accessible from a LexBIGService.</p> <div>  Note Only generic extensions (base class GenericExtension) will be listed here. All other classes are retrievable at the appropriate interface point (filter, sort, etc). </div>
Input:	<i>none</i>
Output:	<i>org.LexGrid.LexBIG.iso21090.DataModel.Collections.ExtensionDescriptionList</i>
Exception:	<i>RemoteException</i>
Implementation Details:	<p>Implementation: <i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call:</p> <ul style="list-style-type: none"> <i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> <i>Step 2:</i> Invoke the LexEVS caGrid service as follows: <pre>ExtensionDescriptionList edl = lbs.getGenericExtensions();</pre>

getGenericExtension

`getGenericExtensions(ExtensionIdentification)`

Description:	Returns an instance of the application-specific extension registered with the given name.
Input:	<i>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.ExtensionIdentification</i>
Output:	<i>org.LexGrid.LexBIG.iso21090.DataModel.Collections.SortDescriptionList</i>
Exception:	<i>RemoteException</i>

Implementation Details:	<p>Implementation : Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call :</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <div>  Note Currently this method will return a <code>LexBIGServiceConvenienceMethods</code> instance. </div> <ul style="list-style-type: none"> Step 2: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.ExtensionIdentification</code> to hold the Extension name. <pre>ExtensionIdentification extension = new ExtensionIdentification(); extension.setLexBIGExtensionName("LexBIGServiceConvenienceMethods");</pre> <ul style="list-style-type: none"> Step 3: Invoke the LexEVS caGrid service as follows: <pre>LexBIGServiceConvenienceMethodsGrid lbscm = lbs.getGenericExtensions(extension);</pre> <ul style="list-style-type: none"> Step 4: Return the <code>LexBIGServiceConvenienceMethodsClient</code> to the user. This <code>LexBIGServiceConvenienceMethodsClient</code> has the above <code>org.LexGrid.LexBIG.Extensions.Generic.LexBIGServiceConvenienceMethods</code> as a Resource. An <code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.service.CodedNodeGraphClient</code> object is built from the above Reference.
--------------------------------	--

getHistoryService

`getHistoryService(CodingSchemeIdentification)`

Description:	Resolve a reference to the history api servicing the given coding scheme.
Input:	<code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code>
Output:	<code>org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.HistoryService.stubs.types.HistoryServiceReference</code>
Exception:	<code>RemoteException</code>
Implementation Details:	<p>Implementation :</p> <ul style="list-style-type: none"> Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Step 2: Return the <code>HistoryServiceClient</code> to the user. This <code>HistoryServiceClient</code> has the above <code>org.LexGrid.LexBIG.History.HistoryService</code> as a Resource. This Client is a Service Context that allows the user to call regular <code>org.LexGrid.LexBIG.History.HistoryService</code> API calls through the grid service. <code>HistoryServiceClient</code> implements the Interface <code>org.LexGrid.LexBIG.History.HistoryService</code>}}e. This makes calling Grid Service Calls through <code>{{org.LexGrid.LexBIG.cagrid.LexBIGCaGridServices.HistoryService.client.HistoryServiceClient</code> transparent to the end user.

Sample Call	<p>Sample Call :</p> <ul style="list-style-type: none"> <i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> <i>Step 2:</i> Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name. <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> <ul style="list-style-type: none"> <i>Step 3:</i> Invoke the LexEVS caGrid service as follows: <pre>HistoryServiceGrid history = lbs.getHistoryService(codingScheme);</pre>
--------------------	--

getSortAlgorithms

`getSortAlgorithms(SortContext)`

Description:	Returns a description of all registered extensions used to provide additional filtering of query results.
Input:	<code>org.LexGrid.LexBIG.iso21090.DataModel.InterfaceElements.types.SortContext</code>
Output:	<code>org.LexGrid.LexBIG.iso21090.DataModel.Collections.SortDescriptionList</code>
Exception:	<code>RemoteException</code>
Implementation Details:	<p>Implementation :</p> <p><i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results.</p> <p>Sample Call :</p> <ul style="list-style-type: none"> <i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code> <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> <i>Step 2:</i> Invoke the LexEVS caGrid service as follows: <pre>SortDescriptionList sortDescList = lbs.getSortAlgorithms(sortContext);</pre>

resolveCodingSchemeCopyright

`resolveCodingSchemeCopyright(CodingSchemeIdentification)`

Description:	Return coding scheme copyright given a specific tag or version identifier.
Input:	<code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code>
Output:	<code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeCopyRight</code>
Exception:	<code>RemoteException</code>

Implementation Details:	<p>Implementation : Step 1: Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call :</p> <ul style="list-style-type: none"> Step 1: Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <ul style="list-style-type: none"> Step 2: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name. <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setCode(code);</pre> <ul style="list-style-type: none"> Step 3: Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.Core.CodingSchemeVersionOrTag</code> containing the Version information for the desired Coding Scheme. <pre>CodingSchemeVersionOrTag csvt = new CodingSchemeVersionOrTag(); csvt.setVersion ("testVersion");</pre> <ul style="list-style-type: none"> Step 4: Invoke the LexEVS caGrid service as follows: <pre>CodingSchemeCopyRight copyright = lbs.resolveCodingSchemeCopyRight(codingScheme, csvt);</pre>
--------------------------------	--

setSecurityToken

`setSecurityToken(CodingSchemeIdentification, SecurityToken)`

Description:	Sets the Security Token for the given Coding Scheme.
Input:	<code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification, gov.nih.nci.evs.security.SecurityToken</code>
Output:	<code>org.LexGrid.LexBIG.cagrid.LexEVSGridService.stubs.types.LexEVSGridServiceReference.LexEVSGridServiceReference</code>
Exception:	<code>RemoteException</code>

Implementation Details:	<p>Implementation : <i>Step 1:</i> Call this method on the associated LexEVS Service instance (or Distributed LexEVS instance) on the server, and forward the results. Sample Call :</p> <ul style="list-style-type: none"> <i>Step 1:</i> Connect to the LexEVS caGrid Service using the <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceAdapter</code> or <code>org.LexGrid.LexBIG.cagrid.adapters.LexBIGServiceGridAdapter</code>. <pre>LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);</pre> <i>Step 2:</i> Build an <code>org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification</code> to hold the Coding Scheme name. <pre>CodingSchemeIdentification codingScheme = new CodingSchemeIdentification(); codingScheme.setName("codingScheme");</pre> <i>Step 3:</i> Build an <code>gov.nih.nci.evs.security.SecurityToken</code> containing the security information for the desired Coding Scheme. <pre>SecurityToken metaToken = new SecurityToken(); metaToken.setAccessToken("token");</pre> <i>Step 4:</i> Invoke the LexEVS caGrid service as follows: This will return a reference to a new "LexBIGServiceGrid" instance that is associated with the security properties that were passed in. <pre>LexBIGServiceGrid lbsg = lbs.setSecurityToken(codingScheme, metaToken);</pre>
--------------------------------	---

Usage Instructions

Service URL

LexEVS Grid Service 4.2 URL:

Link provided for historical purposes <http://lexevsapi.nci.nih.gov/wsrf/services/cagrid/LexEVSGridService>

The service is also accessible via:

[caGRID Portal](#)

Required Libraries

The libraries required for programmatic access to the LexEVS Grid Service are listed in the tables below. The 3rd Party Software Libraries required for use of the LexEVS API Grid Service are listed in the following table.

Product	Jars	License	Home Page
Apache WS-Addressing	addressing-1.0.jar	adressing 1.0.LICENSE	From Globus 4.0.2 Java Web Services Core lib directory: http://www.globus.org/toolkit/downloads/4.0.2 Source available at: <div> Link provided for historical purposes http://ws.apache.org/addressin </div>

Apache Axis	<ul style="list-style-type: none"> • axis-ant.jar • axis.jar • commons-pool-1.3.jar • commons-logging-1.1.jar • commons-lang-2.2.jar • commons-collections-3.2.jar • commons-codec-1.3.jar • log4j-1.2.8.jar • jaxrpc.jar • saaj.jar • wsdl4j.jar 	axis-jars.LICENSE	http://ws.apache.org/axis
Apache Xerces	xercesImpl.jar	xerces.LICENSE	http://xerces.apache.org/xerces-j
Apache Lucene	<ul style="list-style-type: none"> • lucene-core-2.3.2.jar • lucene-regex-2.3.2.jar • lucene-snowball-2.3.2.jar 	Lucene LICENSE	http://lucene.apache.org/
ASM - all purpose Java bytecode manipulation and analysis framework	asm.jar	http://asm.objectweb.org/license.html	http://asm.objectweb.org/
Castor	castor-1.2.jar	Link provided for historical purposes http://www.castor.org/license.html	Link provided for historical purposes http://www.castor.org/index.html
Globus Toolkit	cog-axis.jar cog-jglobus.jar	http://www.globus.org/toolkit/legal/4.0/	
Bouncy Castle Crypto APIs	jce-jdk13-125.jar	http://www.bouncycastle.org/licence.html	http://www.bouncycastle.org/
Open Permis	wsrf_core.jar wsrf_core_stub s.jar	http://www.openpermis.org/BSDlicenceKent.txt	http://www.openpermis.org/
Apache WSS4J	wss4j.jar	http://ws.apache.org/wss4j/license.html	http://ws.apache.org/wss4j/
Spring	spring.jar	Spring LICENSE	http://www.springframework.org

The NCICB software captured under the caBIG® umbrella are listed in the following table.

Library	Associated JARs
caGrid Software Libraries	caGrid-ServiceSecurityProvider-client-1.2.jar
caGrid Software Libraries	caGrid-ServiceSecurityProvider-common-1.2.jar
caGrid Software Libraries	caGrid-ServiceSecurityProvider-stubs-1.2.jar
caGrid Software Libraries	caGrid-core-1.2.jar
caGrid Software Libraries	caGrid-metadata-common-1.2.jar
caGrid Software Libraries	caGrid-metadata-data-1.2.jar
caGrid Software Libraries	caGrid-metadata-security-1.2.jar
caGrid Software Libraries	caGrid-metadatautils-1.2.jar

EVS API Libraries	evsapi42-beans.jar
EVS API Libraries	evsapi42-framework.jar
LexEVS Grid Service Client Library	LexEVSGridService-client.jar
LexEVS Grid Service Stubs	LexEVSGridService-stubs.jar
LexEVS Grid Service Common	LexEVSGridService-common.jar
LexEVS Grid Service Service	LexEVSGridService-service.jar
LexEVS Grid Service Tests	LexEVSGridService-tests.jar
caCORE SDK Library	sdk-client-framework.jar
LexEVS API	lexbig.jar
Custom Castor Serializer	castor-bean-serializer.jar

Downloads

For your convenience, the required libraries are available for download here:

[Required Libraries](#)

In order to programmatically access the LexEVS API Grid Service, these libraries need to be added to your local classpath.

Code Examples

Example Client and Service Calls, and SOAP Messages

See [zip file](#).

Example API Usage

Example 1: Searching for concepts in NCI Thesaurus containing the string "Gene."

Java Code Snippet

```
//Create a Connection to the Grid Service
LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(gridServiceURL);

//Set up the CodingSchemeIdentification object to define the Coding Scheme</font>
CodingSchemeIdentification csid = new CodingSchemeIdentification();
csid.setName("NCI Thesaurus");

//Get the CodedNodeSet for that CodingScheme (This returns a CodedNodeSet Service Context)
CodedNodeSetGrid cns = lbs.getCodingSchemeConcepts(csid, null);
//getCodingSchemeConcepts is a Grid Service Call

//Set the text to match
MatchCriteria matchText = new MatchCriteria();
matchText.setText("Gene");
//Define a SearchDesignationOption, if any
SearchDesignationOption searchOption = new SearchDesignationOption();

//Choose an algorithm to do the matching
ExtensionIdentification matchAlgorithm = new ExtensionIdentification();
matchAlgorithm.setLexBIGExtensionName("contains");

//Chose a language
LanguageIdentification language = new LanguageIdentification();
language.setIdentifier("en");

//Restrict the CodedNodeSet
cns.restrictToMatchingDesignations(matchText, searchOption, matchAlgorithm, language);
//restrictToMatchingDesignations is a Grid Service Call

//Create a SetResolutionPolicy to handle the details of Resolving the CodedNodeSet
//Here, we will set the Maximum number of Concepts returned to 10.
SetResolutionPolicy resolvePolicy = new SetResolutionPolicy();
resolvePolicy.setMaximumToReturn(10);

//Do the resolve
ResolvedConceptReferenceList rcrl = cns.resolveToList(resolvePolicy);
//resolveToList is a Grid Service Call

//Use the returned ResolvedConceptReferenceList to print some details about the concepts found
ResolvedConceptReference[] rcrlarr = rcrl.getResolvedConceptReference();
for (int i = 0; i < rcrlarr.length; i++) {
    System.out.println(rcrlarr[i].getConceptCode());
    System.out.println(rcrlarr[i].getReferencedEntry().
        getPresentation()[0].getText().getContent());
}
```

Error Handling

Error Connecting to LexEVS Grid Service

When connecting through the Java Client, `java.net.ConnectException` and `org.apache.axis.types.URI.MalformedURIException` may be thrown upon an unsuccessful attempt to connect.

A `MalformedURIException` is thrown in the case if a poorly-formed URL string. In this case, the exception is thrown before an attempt to connect is even made.

If the URL is well-formed, proper connection is tested. If the connection attempt fails, a `ConnectException` is thrown containing the reason for the failure.

Java Code

```
try{
    LexBIGServiceGridAdapter lbsg = new LexBIGServiceGridAdapter
        ("http://localhost:8080/wsrf/services/cagrid/LexEVSGridService");
} catch(java.net.ConnectException e){
    //Error Connecting
    e.printStackTrace();
} catch(org.apache.axis.types.URI.MalformedURIException e){
    //URL Syntax Error
    e.printStackTrace();
}
```

This example shows a typical connection to the LexEVS Grid Service, with the two potential Exceptions being caught and handled as necessary.

LexEVS Errors

LexEVS errors will be forwarded through the Distributed LexEVS layer and then on to the Grid layer. Input parameters, along with any other LexEVS (or Distributed LexEVS) errors will be detected on the server, not the client, and forwarded. All Generic LexEVS (or Distributed LexEVS) errors will be forwarded via a RemoteException, with the cause of the error and underlying LexEVS error message included.

Invalid Service Context Access

Service Context Services are not meant to be called directly. If the client attempts to do so, an org.LexGrid.LexBIG.cagrid.LexEVSGridService.CodedNodeSet.stubs.types.InvalidServiceContextAccess Exception will be thrown. This indicates a call was made to a Service Context without obtaining a Service Context Reference via the Main Service (see the above section Service Contexts and State for more information).

Security Issues

LexEVS Grid Service Security

Certain vocabulary content accessible through the LexEVS Grid Service may require extra authorization to access. Each client is required to supply its own access credentials via Security Tokens. These Security Tokens are implemented by a SecurityToken object:

Name: SecurityToken
Namespace: gme://caCORE.caCORE/3.2/gov.nih.nci.evs.security
Package: gov.nih.nci.evs.security

Accessing Secure Content

A client establishes access to a secured vocabulary via the following Grid Service Calls:

- *Step 1:* Connect to the LexEVS caGrid Service
LexBIGServiceGrid lbs = new LexBIGServiceGridAdapter(url);
- *Step 2:* Build an org.LexGrid.LexBIG.iso21090.DataModel.cagrid.CodingSchemeIdentification to hold the Coding Scheme name.

```
CodingSchemeIdentification codingScheme = new CodingSchemeIdentification();
codingScheme.setName("codingScheme");
```

- *Step 3:* Build an gov.nih.nci.evs.security.SecurityToken containing the security information for the desired Coding Scheme.
SecurityToken token = new SecurityToken();
token.setAccessToken("securityToken");
- *Step 4:* Invoke the LexEVS caGrid service as follows: This will return a reference to a new "LexBIGServiceGrid" instance that is associated with the security properties that were passed in.

```
LexBIGServiceGrid lbsg = lbs.setSecurityToken(codingScheme, token);
```

It is important to note that the Grid Service "setSecurityToken" returns an {{org.LexGrid.LexBIG.cagrid.LexEVSGridService.stubs.types.LexEVSGridServiceReference.LexEVSGridServiceReference}} object. This reference must be used to access the secured vocabularies.

Implementation

Each call to "setSecurityToken" sets up a secured connection to Distributed LexEVS with the access privileges included in the SecurityToken parameter. The LexEVSGridServiceReference that is returned to the client contains a unique key identifier to the secure connection that has been created on the server. All subsequent calls the client makes through this LexEVSGridServiceReference will be made securely. If additional SecurityTokens are passed in through the "setSecurityToken" Grid Service, the additional security will be added and maintained.

The "setSecurityToken" Grid Service is a stateful service. This means that after the client sets a SecurityToken, any subsequent call will be applied to that SecurityToken.

Secure connections are not maintained on the server indefinitely, but are based on load conditions. The server will allow 30 unique secure connections to be set up for clients without any time limitations. As additional requests for secure connections are received by the server, connections will be released by the server on an 'oldest first' basis. No connection, however, may be released prior to 5 minutes after its creation.

If no SecurityTokens are passed in by the client, a non-secure Distributed LexEVS connection will be used. The server maintains one (and only one) un-secured Distributed LexEVS connection that is shared by any client not requesting security.



Note

All non-secured information accessed by the LexEVS Grid Service is publicly available from NCICB and users are expected to follow the licensing requirements currently in place for accessing and using NCI EVS information.